



Instructions for Catalog # 649
Wisconsin Gasoline Range Organics (GRO/PVOC) in Water
Revision 112211

Description:

- This standard is packaged in a 2 mL flame-sealed ampule containing approximately 2 mL of standard concentrate.
- This concentrate is not preserved.
- The solvent for this concentrate is Methanol.
- The concentrate should be stored at $4\pm 2^{\circ}\text{C}$.
- The diluted standard will contain all or a subset of the analytes listed in the ranges specified on the data reporting form.

Before you begin:

- This standard has been prepared as a concentrate and must be diluted prior to analysis.
- This standard has been designed to meet all specifications of the State of Wisconsin Laboratory Certification and Registration Program.
- As the diluted standard is not stable, it must be analyzed **immediately** after the concentrate is diluted.
- Naphthalene is present in the standard, but is not required for WI PVOC reporting.

Instructions:

1. Add 100 mL of organic free, deionized water to a clean 100 mL class A volumetric flask.
2. Carefully snap the top off of the Wisconsin Gasoline Range Organics (GRO/PVOC) in Water ampule.
3. Using a clean, dry, class A pipet or a syringe, transfer 5.0 μL of the concentrate below the surface of the water in the flask.
4. Cap the flask and mix by inverting two or three times.
5. Immediately analyze the diluted sample by your normal procedures.
6. Report your results as $\mu\text{g/L}$ for the diluted sample.

Safety:

ERA products may be hazardous and are intended for use by professional laboratory personnel trained in the competent handling of such materials. Responsibility for the safe use of these products rests entirely with the buyer and/or user. Material Safety Data Sheets (MSDS) for all ERA products are available by calling 1-800-372-0122.